

DESCRIPTION

2-in-1 paint for ceilings and interior walls in drywall.

SPECIFICATIONS**TECHNICAL**

Performance ¹	1,345 ft (125 m ²)
Drying	1 hour
Repaint	2,4 hours

SHIPMENT

Product	Sealant and paint
Brand	GYPTEX
Presentation	Gallon and 5 Gal bucket

DETAIL**BENEFITS**

Get to know our paint that help you deliver your projects faster.

- Get high coverage
- Reduces imperfections
- Contains more solids
- Resists moisture
- Conceals joints' shadows
- Fills porosities
- Save costs

CHARACTERISTICS

- Primer & Paint
- Ultra matte finish
- Antifungal protection
- High color retention
- Optimum adherence
- Excellent leveling
- Higher performance

USE

- Roofs
- Walls

SURFACES

- Drywall
- Cement
- Stucco
- Brick
- Fiber cement
- Wood

COMPOSITION

Vinyl-acrylic copolymer resin.

APPLICATION**Surface preparation**

Make sure the work surface to be painted is clear of irregularities, defects or dampness. Remove old layers of paint and patch cracks or fissures. The surfaces must be well patched, sanded, clean, dry and free of lime, dust or grease before applying the paint.

If there are fungi, green or gray slime (mold) on the surface to be painted, it can be washed with a 5% sodium hypochlorite solution, applying it with plastic or wire bristle brushes, leaving it to act for at least 20 minutes. Wash the entire surface with plenty of water and allow to dry completely.

Painting and dilution

Shake the paint before use or stir with a spatula until completely homogenized. Dilute the product by adding 25% of its volume in water. If applying a single coat, do not dilute or thin. COVER-98 can be applied by brush, roller, or airless equipment, allowing approximately 2 to 3 hours to dry for a second coat.

STORAGE

COVER-98 has a shelf life of 12 months under normal storage conditions from its date of manufacture, it must be kept in a sealed container and away from heat sources.

RECOMMENDATIONS

During the application, personal protection elements must be used (glasses, gloves and suitable clothing).



PERFORMANCE TABLE

PHYSICOCHEMICAL CHARACTERISTICS

Product performance may vary based on applicator skill and experience.

Higher yields are possible under optimal conditions.

SURFACE	sf x gal
Drywall	215 - 269
Plastic stucco	215 - 269
Paint over different color	322 - 430
Paint over similar color	430 - 538

COVER-98 is designed to be applied in light construction systems, both as a primer base and as a final finish.

PROPERTY	VALUE
Stomer viscosity	110 - 120 KU A 25°C
Solids (V / V)	34% min.
Dispersion fineness	4 Hegman min.
Weight per gallon	5,4 Kg
Microbiological resistance	Without fungus
Drying time	4 hours max.
Chalking	Does not present
Opacity / Coverage	97% min.